


CANTY

PROCESS TECHNOLOGY


IMMERSION TURBIDITY / COLOR ANALYSIS / PERCENT SOLIDS ANALYZER

THE SOLUTION



Combining the latest in CCD Ethernet camera technology with Canty fused glass, lighting and CANTYVISIONCLIENT™ software, the Immersion Analyzer System provides real time, in-line measurement of either turbidity, color analysis or percent solids, determined by the P/N purchased.

No sampling or lab analysis is required! Each unit can be *fully* integrated into existing TCP/IP networks. CANTYVISIONCLIENT™ software is installed on a user-supplied PC, and connected to the in-line measurement system via Ethernet network. Images of the process can now be seen at any networked PC. The live images are remotely analyzed by CANTYVISIONCLIENT™ software. A comprehensive library of standard utilities and data functions provide a multitude of *real-time* process information.



The CANTY Immersion Turbidity, Color Measurement or Percent Solids Measurement System uses a variable insertion measurement gap, which is unique to the Canty system. Our unique fused glass seal allows our equipment to be easily submersed into the product for quick, highly accurate process measurement. The image process can be setup with multiple zone sensing on the image of the fluid thus comparing results for reliability and allowing immediate detection of any problem.

FEATURES

- Ethernet Connectivity For Measurement
- Ergonomic Immersion Package
- Fused Glass Seals Instrument from Process
- Regulated High Intensity Light Source
- 316L SS and Anodized Aluminum Wetted Material
- Rugged, Industrial Sensor
- Easy to Operate

ADVANTAGES

- No Lab Sampling Required
- Low Cost Measurement System
- Provides Both A Real Time Measurement And A Continuous Real Time View
- Fully Cleanable Unit
- Digital Video Storage to Customer PC
- Low Cost Measurement System

COMMON APPLICATIONS

- Effluent Turbidity Measurement


CANTY

Buffalo, NY USA
Ph: (716) 625 4227

Dublin, Ireland
Ph: + 353 (01) 882 9621

Phuket, Thailand
Ph: + 66 (83) 968 9548

TYPICAL PACKAGE



Notes:

1. Camera/Light PSU Enclosure not shown. Portable integrated PSU is provided in NEMA type 4 enclosures typ. and must be located within 100 feet of sensor.
2. Customer PC to install CANTYVISIONCLIENT™ Software is not included. Reference datasheet TA10592-1. Alternatively see the [VCM datasheet](#).
3. Approximate Weight : 18 lbs.

HOW TO ORDER

Ordering Information

HOW TO ORDER: Select the appropriate symbols and build a part number as shown:

EXAMPLE:

VDTA501

APPLICATION

T - Turbidity
C - Color Analysis
P - Percent Solids

ENVIRONMENTAL RATING

1 - NEMA4 WP
2 - IP66

IMMERSION HANDLE LENGTH

3 - 3 ft.
4 - 4 ft.
5 - 5 ft.
6 - 6 ft.

INPUT POWER

0 - 120V AC, 60Hz, 250 W
1 - 230V AC, 50Hz, 250 W

For additional information on the Vector Control Module, please see the [VCM Datasheet](#).

CANTY

Buffalo, NY USA
Ph: (716) 625 4227

Dublin, Ireland
Ph: + 353 (01) 882 9621

Phuket, Thailand
Ph: + 66 (83) 968 9548