

Turbidity Appl	ication Questi	onnaire - Engir	neering Informa	ation
Company:		Date:		
Contact name:		Address:		
Phone:		Email:		
Canty job #:		PO#:		
Connection type:	□Tri-Clamp □Tube Diameter	□Swagelock □ NPT (fema	□Flange(/ le)	ANSI/DIN)
Connection size (1/4" - 8" +)				
Spray ring cleaning mechanism:	□Yes □No **Not applicable for Tri-Clamp connections. Recommended for batch purposes. Typically not needed in continuous applications.			
Environmental rating:	□NEMA 4 Weather	proof □IP 66	Explosion proof	□Flame proof
Pressure & Temperature rating:				
NTU range:				
Concentration range (ppm):	Dissolved □Suspended			
% solids (if applicable):				
Material / process:				
What does the process liquid look like when favorable?				
What does the process liquid look like when unfavorable?				
Wetted gasket material:	□Buna □Viton	□Silicone □EPDM	□Neoprene □ Kal	rez □Chemrez
Wetted metal material:	□316L Stainless ste	eel □Hastelloy C276	or equal □Hastelloy	C-22 or equal
Currently used methods of measurement:				
Additional notes or relevant sketches:				
*** FOR COLOR APPLICATIONS ONLY ***				
Color scale used:	□Saybolt □ AS	TM DOther:	Range	e:
Color application:	□Color removal □Other	□Color addition	□Color avoidance	□Blending
Color measurement type:	□Repeatable color □Change in color			

	TT	P 7
LA		IY