

CANTY

PROCESS TECHNOLOGY

SOLIDSIZER™ - TS SOLID PARTICLE ANALYSIS SYSTEM



FEATURES

- Particle distribution by major, minor diameter, area, perimeter available with Canty CoreUnit™.
- Remote processor control of system settings.
- Variable lens magnification (sub micron through boulders-no upper size limit). Consult factory for details.
- Fiber optic backlighting for true shape illumination. Front lighting for color detection.
- Shape analysis.
- Optional light filters available for wavelength sensitive materials.
- Tilt tray for flat particle analysis.

SYSTEM DESIGN

The Canty SolidSizer TS unit is a versatile tool for lab environments to determine particle size and shape, thereby eliminating the need for sieving. The system also has multiple configurations that allow color analysis and defect detection, as well as a tilting stage for flat particle analysis.

THE CANTY ADVANTAGE

The SolidSizer TS is a vision based sensor that combines with the Canty Vector processor to provide a complete particle analysis system. Operating features are remotely controlled at the processor screen view and include zoom, calibration, feed speed and level control, as well as all camera functions such as shutter, gain and resolution. The system comes with back and front lighting for maximum versatility. The modular design allows for easy assembly of different configurations depending upon product type and/or analysis desired. The tilt stage feature is similar to the technology patented in the Canty RockSizer and is especially effective for analyzing flat, stone-like particles. The stage is designed for both back and front lighting use.

APPLICATIONS

- Pharmaceutical powders
- Polymer pellets and beads
- Agricultural products
- Aggregates
- Color analysis
- Glass bead applications
- Color/black speck detection
- Agglomeration control
- Spray dryers and fluid bed applications
- Replaces existing lab screen/sieve systems
- End product Q.C. and lot certification
- Many, many more!

SPECIFICATIONS

- Power: 120 VAC / 60 Hz (230 VAC / 50 Hz)
- Shutter Speed: variable up to 1/100,000 sec
- Instrument Air: 20 to 30 PSI when required


BENEFITS

- Virtually Eliminates Lab Screening Labor
- Output Matches Sieve/Screen Data - Direct Replacement
- Three Month Pay Back

Ordering Information

HOW TO ORDER: Select the appropriate symbols and build a part number as shown:

EXAMPLE:



CoreUnit™